

Radiative Transfer Modeling for CoBOP

Curtis D. Mobley
Sequoia Scientific, Inc.
Westpark Technical Center
15317 NE 90th Street
Redmond, WA 98052
phone: 425-867-2464 x 109 fax: 425-867-5505 email: mobley@sequoiasci.com

Award Number: N0001497C0018
http://www.onr.navy.mil/sci_tech/ocean/onrpgahk.htm

LONG-TERM GOAL

The overall goal of this work is to take oceanic radiative transfer theory into a new domain: optically shallow waters with spatially variable bottom optical properties, including sloping bottoms and non-Lambertian bottom bidirectional reflectance distribution functions.

OBJECTIVES

Currently available models for analysis of hyperspectral remote sensing imagery in shallow waters almost always assume that the bottom is a level, homogeneous, Lambertian reflecting surface—a spatially homogeneous surface at a constant depth whose reflected radiance appears the same from all viewing directions. The first objective of this year's work was to quantify the extent to which non-Lambertian bottoms can affect upwelling radiances as would be detected by above-water sensors. Many studies of marine light fields also assume the water and bottom optical properties to be horizontally homogeneous, which is not the case in shallow waters with patchy or sloping bottoms. The second objective this year was to quantify the extent to which patchy or sloping bottoms influence the water-leaving radiance. In particular, I wished to see when a 1-D (horizontally homogeneous, constant depth) radiative transfer model is sufficient, and when a computationally expensive 3-D Monte Carlo model must be used.

APPROACH

The Hydrolight radiative transfer model (<http://www.sequoiasci.com>; Mobley and Sundman, 2001a,b) allows for non-Lambertian bottom boundaries. However, because of the lack of measured bidirectional reflectance distribution functions (BRDFs; Mobley, Zhang, and Voss, 2001; Zhang et al., 2001) for actual ocean bottom materials, Hydrolight's mathematical capability had not been previously exploited. This year, non-Lambertian BRDFs were used in Hydrolight to simulate the effects of horizontally uniform but non-Lambertian bottoms on in-water and water-leaving radiances.

The Hydrolight model requires the water and the surface and bottom boundaries to be horizontally homogeneous; Hydrolight is therefore not applicable to shallow waters with spatially variable or sloping bottoms. To simulate the inherently 3-D light fields due to the effects of spatially variable or sloping bottoms, Monte Carlo models must be used.

Report Documentation Page			Form Approved OMB No. 0704-0188		
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE 30 SEP 2001		2. REPORT TYPE		3. DATES COVERED 00-00-2001 to 00-00-2001	
4. TITLE AND SUBTITLE Radiative Transfer Modeling for CoBOP				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Sequoia Scientific, Inc., Westpark Technical Center,,15317 NE 90th Street,Redmond,,WA, 98052				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT The overall goal of this work is to take oceanic radiative transfer theory into a new domain: optically shallow waters with spatially variable bottom optical properties, including sloping bottoms and non-Lambertian bottom bidirectional reflectance distribution functions.					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT Same as Report (SAR)	18. NUMBER OF PAGES 9	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

WORK COMPLETED

This last year of CoBOP work was used to conclude the model development and studies begun in earlier years, and to prepare and submit papers on that work. In particular, non-Lambertian BRDFs were used to simulate radiances for situations of interest to the airborne Portable Hyperspectral Imaging Low-Light Spectrometer (PHILLS) system, which played a major role in the CoBOP field programs (Davis et al., 1999). BRDFs as measured by K. Voss for ooid sand and grapestone were used for simulations of bare substrates, and various analytical BRDFs developed for terrestrial plant canopies were used as proxies for seagrass BRDFs, which were not measured in the CoBOP field experiments.

A Backward Monte Carlo model was developed to simulate 3-D radiance distributions caused by spatially variable bottom reflectances (such as patchy sand and seagrass bottoms) and by sloping or rippled bottoms. The mathematical techniques are described in Gordon (1985), Mobley (1994, Section 6.2), and Mobley and Sundman (2001c). This model, called BMC3D, allows the user to specify an arbitrary spatial pattern of bottom BRDFs (which can be non-Lambertian) as well as sensor location, viewing direction, and field of view.

Results of my work are described in three papers that have been submitted to the CoBOP special issue of *Limnology and Oceanography* (Mobley, Zhang, and Voss, 2001; Mobley and Sundman, 2001c; Voss et al., 2001). In addition to the work explicitly described here, I authored or co-authored three other papers (Hoge et al., 2000; Leathers et al., 2001; Mobley, Sundman, and Boss, 2001) and three book chapters (Bissett et al., 2001; Mobley 2001a,b) that contribute to the overall goals of CoBOP or to other Navy needs; three papers were presented at Ocean Optics XV.

RESULTS

Figure 1 (from Mobley, Zhang, and Voss, 2001) shows an example of Hydrolight simulations of the errors that occur in predictions of the water-leaving radiance L_w (the quantity of interest in remote sensing) if a non-Lambertian bottom is replaced by a Lambertian bottom *having the same irradiance reflectance R* . The non-Lambertian bottoms referenced in this figure include a measured BRDF of ooid sand at the CoBOP field site, an analytical BRDF with parameters chosen to simulate sand (Hapke, 1993, Eq. 8.89), and semianalytical BRDFs of a wheat field and coniferous forest (Rahman, *et al.*, 1993), which were used as proxies for a seagrass BRDF, the exact form of which is unknown. The water-column optical properties were taken from measured values at the CoBOP Bahamas site. To accentuate the bottom effects, the water was only 1 m deep and the sun was at 50 deg from the zenith. These errors thus represent a worse-case situation of very shallow water and large solar angle. The errors become smaller as the bottom becomes deeper or the sun approaches the zenith. θ_v and ϕ_v are the polar and azimuthal viewing directions, respectively. The viewing directions seen in a PHILLS scan are shown in green. The sun was located at $(\theta_v, \phi_v) = (50^\circ, 180^\circ)$.




Fig. 1. *Contours show the percent errors in water-leaving radiance that result from replacing a non-Lambertian BRDF with a Lambertian BRDF having the same irradiance reflectance. Green boxes show the PHILLS viewing directions. [For directions relevant to remote sensing, the errors are less than 10%]*

Simulations like those of Fig. 1 yield the first important conclusion of my work:

For solar and viewing directions relevant to most ocean-color remote sensing, a non-Lambertian bottom can be modeled as a Lambertian bottom *having the same irradiance reflectance* $R = E_u/E_d$, with errors of less than 10% in L_w .

Thus the different *angular* bottom reflectance patterns do not make much difference in the signals received by the PHILLS sensor. *The crucial measurement that optically describes a bottom type is the irradiance reflectance.*

Figure 2 (from Mobley and Sundman, 2001c) shows a BMC3D simulation of the upwelling irradiance E_u at the surface, as would result from moving an irradiance sensor across a boundary between bottom types having $R = 0.05$ (e.g., seagrass) and $R = 0.5$ (e.g., bright sand). E_u is sometimes used in remote sensing studies because it is easily measured and can be related to the upwelling radiance. The bottom was at a depth of 5 m, and the water IOPs were the same as used for Fig. 1. The green lines in the figure show the Hydrolight-computed values for infinite grass and infinite sand bottoms for comparison. The blue line shows E_u as computed by BMC3D. In this simulation, the instrument begins “seeing” the boundary at a horizontal distance of roughly twice the water depth. The red line shows E_u computed using the simple 1D model of Eqs. (1) and (2) below.




Fig. 2. E_u as a function of horizontal position near a boundary between bottoms of different reflectances.

In Fig. 2, the exact (to within statistical noise) BMC3D calculations required hours of computer time; the Hydrolight calculations took less than 5 seconds. It would therefore be computationally desirable to have an approximate model that could use the Hydrolight 1D solutions for the two different bottoms in combination with the sensor viewing geometry to predict E_u (or other quantities) near such boundaries. Such a 1D model was developed from simple radiative transfer approximations. The model, when applied to the situation seen in Figs. 2 and 3, has the form

$$E_u(x) = w(x;1) E_u(1D;1) + w(x;2) E_u(1D;2), \quad (1)$$

where

$$= \frac{\int_{\Xi} - \cos \theta \, d\Omega}{\int_{\Xi} - \cos \theta \, d\Omega} \quad (2)$$

In Eqs. (1) and (2), $E_u(1D;i)$ is the 1D (Hydrolight) solution for bottom type i , $S(\theta)$ is the sensor response function [$S(\theta) = \cos \theta$ for a measurement of E_u], c is the beam attenuation of the water, and the integration over $\Xi(i)$ means “integrate over the directions where the sensor at location x sees bottom type i .” As seen in Fig. 2, the simple 1D model of Eqs. (1) and (2) gives rather good predictions of the 3D situation; in this simulation, the difference between the 1D model and the exact 3D calculation was less than 10%. Additional simulations such as this yield the second important conclusion of this work:

Using a 1D radiative transfer model such as Hydrolight to predict E_u or L_u can give errors of many tens of percent near the boundary of highly contrasting bottom types. However, a simple analytical model that weights the 1D solutions according to the sensor response and location can reduce these errors to roughly 10%.

A similar statement can be made about sloping bottoms, in which case a sloping bottom can be modeled as a level bottom using Hydrolight with a correction for the change in the incident angle of the sun's unscattered beam onto the bottom.

IMPACT/APPLICATION

Inverse models are being developed by other ONR investigators to retrieve bottom depths and bottom classification information from hyperspectral ocean color sensors such as PHILLS. Those retrieval algorithms generally assume the bottom to be a level, Lambertian reflector. Radiative transfer simulations like those shown here allow the proposed inversion algorithms to be evaluated for patchy, sloping, non-Lambertian bottom boundaries.

The 3-D vs. 1-D simulations allow a determination of when a computationally efficient 1-D model like Hydrolight can be used to simulate the ocean optical environment, and when a much more expensive 3-D Monte Carlo model must be run. The BMC3D model developed here also allows for simulations of particular sensor geometries (such as sensor angular response), which cannot be exactly simulated in models such as Hydrolight.

TRANSITIONS

1. The BMC3D code was transitioned to Dr. Curtiss Davis of NRL Code 7212 for use in computing the effects of instrument self-shading on the buoyed sensors, which are used to acquire sea-truth data for evaluation of hyperspectral ocean-color remote sensing systems. Those results are described in Leathers et al. (2001).
2. The BMC3D code was transitioned to Dr. Vladimir Haltrin of NRL Code 7331 for use in various simulations of underwater 3D light fields.
3. The BMC3D code was used by Mr. Richard Tompkins of the Office of Naval Intelligence (ONI-241) to simulate the visibility of underwater objects.
4. The BMC3D code is being used by Todd Bowers at the Stennis Space Center to analyze underwater visibility data.

RELATED PROJECTS

Measurements of BRDFs for various bottom types were made by K. Voss (Zhang et al., 2001), and measurements of water and bottom optical properties and associated light fields were made by various investigators in the CoBOP program. Their data were used in conjunction with my models to evaluate the results of the optical closure experiment conducted during the 2000 field experiment (Voss et al., 2001).

REFERENCES

- Bissett, W. P., O. Schofield, C. D. Mobley, M. F. Crowley, and M. A. Moline, 2001. Optical remote sensing techniques in biological oceanography. Invited chapter in *Methods in Microbiology Vol. 30: Marine Microbiology*, J. H. Paul, Editor, 519-538.
- Davis, C. O., M. Kappus, J. Bowles, J. Fisher, J. Antoniadis, and M. Carney, 1999. Calibration, characterization and first results with the Ocean PHILLS hyperspectral imager. Proc. SPIE Conf. on Imaging Spectrometry V, SPIE Vol. 3753: 160-168.
- Gordon, H. R., 1985. Ship perturbation of irradiance measurements at sea. 1: Monte Carlo simulations, *Appl. Opt.* **24**(23), 4172-4182.
- Hapke, B., 1993. *Theory of Reflectance and Emittance Spectroscopy*, Cambridge Univ. Press, 455 pages.
- Hoge, F. E., C. D. Mobley, L. K. Sundman, and P. E. Lyon, 2000. Radiative transfer equation inversion: retrieval of oceanic inherent optical properties. *J. Geophys. Res.*, submitted.
- Leathers, R. A., T. V. Downs, and C. D. Mobley, 2001. Self-shading correction for upwelling sea-surface radiance measurements made with buoyed instruments. *Optics Express*, **8**, 561-571.
- Mobley, C. D., 1994. *Light and Water: Radiative Transfer in Natural Waters*. Academic Press, 592 pages.
- Mobley, C. D. 2000a. *Radiative Transfer in the Ocean*, Invited chapter in *Encyclopedia of Ocean Sciences*, Academic Press, 2001.
- Mobley, C. D., 2001b. Invited contributions to *Dictionary of Geophysics, Astrophysics, and Astronomy*, R. Matzner, editor. CRC Press.
- Mobley, C. D. and L. K. Sundman, 2001a. Hydrolight 4.2 Users' Guide. Sequoia Scientific, Inc., Redmond, WA, 87 pages.
- Mobley, C. D. and L. K. Sundman, 2001b. Hydrolight 4.2 Technical Documentation. Sequoia Scientific, Inc., Redmond, WA, 76 pages.
- Mobley, C. D. and L. K. Sundman, 2001c. Effects of optically shallow bottoms on upwelling radiances: Effects of inhomogeneous and sloping bottoms. *Limnol. Oceanogr.*, submitted.
- Mobley, C. D., L. K. Sundman, and E. Boss, 2001. Phase function effects on oceanic light fields, *Appl. Optics*, submitted.
- Mobley, C. D., H. Zhang, and K. J. Voss, 2001. Effects of optically shallow bottoms on upwelling radiances: Bidirectional reflectance distribution function effects. *Limnol. Oceanogr.*, submitted.

Rahman, H., B. Pinty, and M. M. Verstraete, 1993. Coupled surface-atmosphere reflectance (CSAR) model 2. Semiempirical surface model usable with NOAA AVHRR data, *J. Geophys. Res.*, 98(D11), 20791-20801.

Voss, K. J., C. D. Mobley, L. K. Sundman, J. Ivey, and C. Mazel, 2001. The spectral upwelling radiance distribution in optically shallow waters. *Limnol. Oceanogr.*, submitted.

Zhang, H., K. J. Voss, R. P. Reid, and E. Louchard, 2001. Bi-directional reflectance measurements of sediments in the vicinity of Lee Stocking Island, Bahamas. *Limnol. Oceanogr.*, submitted.

PUBLICATIONS

Max, N., C.D. Mobley, B. Keating, and E.-H. Wu, 1997. Plane-parallel radiance transport for global illumination in vegetation. *Rendering '97*, J. Dorsey and P. Slusallek, editors, Springer Verlag.

Mobley, C.D. and D. Stramski, 1997. Effects of microbial particles on oceanic optics: Methodology for radiative transfer modeling and example simulations. *Limnol. Oceanogr.*, 42(3), 550-560.

Stramski, D. and C.D. Mobley, 1997. Effects of microbial particles on oceanic optics: A database of single-particle optical properties. *Limnol. Oceanogr.*, 42(3), 538-549.

Berwald, J., D. Stramski, C.D. Mobley, and D.A. Kiefer, 1998. The effect of Raman scattering on the average cosine and diffuse attenuation coefficient of irradiance in the ocean. *Limnol. Oceanogr.*, 43(4), 564-576.

Lee, Z. P., K. L. Carder, C. D. Mobley, R. G. Steward, and J. S. Patch, 1998. Hyperspectral remote sensing for shallow waters: 1. A semi-analytical model. *Applied Optics*, 37(27), 6329-6338.

Maffione, R.A., J.M. Voss, and C.D. Mobley, 1998. Theory and measurements of the complete beam spread function of sea ice. *Limnol. Oceanogr.*, 43(1), 29-33.

Mobley, C.D., G.F. Cota, T.C. Grenfell, R.A. Maffione, W.S. Pegau, D.K. Perovich, 1998. Modeling light propagation in sea ice. *IEEE Trans. Geosci. Rem. Sens.*, 36(5), 1743-1749.

Perovich, D.K., J. Longacre, D.G. Barber, R.A. Maffione, G.F. Cota, C.D. Mobley, A.J. Gow, R.G. Onstott, T.C. Grenfell, W.S. Pegau, M. Landry, and C.S. Roesler, 1998. Field observations of the electromagnetic properties of first-year sea ice, *IEEE Trans. Geosci. Rem. Sens.*, 36(5), 1705-1715.

Stephany, S., F. M. Ramos, H. F. de Campos Velho, and C. D. Mobley, 1998. A Methodology for internal light source estimation, *Computer Model. Simul. Eng.*, 3(3), 161-165.

Lee, Z. P., K. L. Carder, C. D. Mobley, R. G. Steward, and J. S. Patch, 1999. Hyperspectral remote sensing for shallow waters: 2. Deriving depths and optical properties by optimization. *Applied Optics*, 38(18), 3831-3843.

Liu, C-C, J. D Woods, and C. D. Mobley, 1999. Optical model for use in oceanic ecosystem models, *Appl. Optics*, 38(21), 4475-4485.

- Mobley, C. D., 1999. Estimation of the remote-sensing reflectance from above-surface measurements. *Appl. Optics*, 38(36), 7442-7455.
- Ohlmann, J. C., D. A. Siegel, and C. D. Mobley, 1999. Ocean radiant heating: 1. Optical influences. *J. Phys. Ocean.*, 30, 1833-1848.
- Tyrrell, T., P.M. Holligan, and C.D. Mobley, 1999. Optical impacts of oceanic coccolithophore blooms. *J. Geophys. Res.*, 104(C2), 3223-3241.
- Flatau, P. J., M. Flatau, J. R. V. Zaneveld, and C. D. Mobley, 2000. Remote sensing of bubble clouds in seawater. *Quart. J. Royal Meteor. Soc.*, 126(568), 2511-2524.
- Hoge, F. E., C. D. Mobley, L. K. Sundman, and P. E. Lyon, 2000. Radiative transfer equation inversion: retrieval of oceanic inherent optical properties. *J. Geophys. Res.*, submitted.
- Stephany, S., F. M. Ramos, H. F. de Campos Velho, and C. D. Mobley, 2000. Identification of inherent optical properties and bioluminescence source term in a hydrologic optics problem. *J. Quant. Spectros. Rad. Trans.*, 67(2), 113-123.
- Stramska, M., D. Stramski, B. G. Mitchell, and C. D. Mobley, 2000. Estimation of the absorption and back-scattering coefficients from in-water radiometric measurements. *Limnol. Oceanogr.*, 45(3), 628-641.
- Bissett, W. P., O. Schofield, C. D. Mobley, M. F. Crowley, and M. A. Moline, 2001. Optical remote sensing techniques in biological oceanography. Invited chapter in *Methods in Microbiology Vol. 30: Marine Microbiology*, J. H. Paul, Editor, 519-538.
- Leathers, R. A., T. V. Downs, and C. D. Mobley, 2001. Self-shading correction for upwelling sea-surface radiance measurements made with buoyed instruments. *Optics Express*, 8, 561-571.
- Mobley, C. D. 2001. *Radiative Transfer in the Ocean*, Invited chapter in *Encyclopedia of Ocean Sciences*, Academic Press, 2001.
- Mobley, C. D., 2001. Invited contributions to *Dictionary of Geophysics, Astrophysics, and Astronomy*, R. Matzner, editor. CRC Press.
- Mobley, C. D. and L. K. Sundman, 2001. Effects of optically shallow bottoms on upwelling radiances: Effects of inhomogeneous and sloping bottoms. *Limnol. Oceanogr.*, submitted.
- Mobley, C. D., H. Zhang, and K. J. Voss, 2001. Effects of optically shallow bottoms on upwelling radiances: Bidirectional reflectance distribution function effects. *Limnol. Oceanogr.*, submitted.
- Mobley, C. D., L. K. Sundman, and E. Boss, 2001. Phase function effects on oceanic light fields, *Appl. Optics*, submitted.
- Voss, K. J., C. D. Mobley, L. K. Sundman, J. Ivey, and C. Mazel, 2001. The spectral upwelling radiance distribution in optically shallow waters. *Limnol. Oceanogr.*, submitted.